



Customer : ESRIN	Document Ref : IDEAS-VEG-IPF-TSP-0543
Contract No : 21525/08/I-OL	Issue Date : 26 January 2010
WP No : 30000	Issue : 1.0

Title : [Envisat Altimetry Data Set Version 2.0] Level 1B and Level 2 processing upgrades

Abstract : Information to be distributed to the user community regarding the processing upgrades performed on the ESA Altimetry NRT and OFL processing chains, respectively implemented in the RA2/MWR IPF v6.02L04 and CMA v9.3

Author : _____
Sabrina Pinori

Approval : _____
David Cotton

Accepted : _____
Pierre Féménias

Distribution :

Hard Copy File:

Filename: IDEAS-SER-IPF-REP-0443_Information to the Users regarding the Envisat RA2-MWR IPF version 6.02L04.doc

Copyright © 2008 VEGA Group PLC

All rights reserved.

No part of this work may be disclosed to any third party translated reproduced copied or disseminated in any form or by any means except as defined in the contract or with the written permission of VEGA Group PLC.

Serco SpA

Tel: +44 (0)1707 391999 **Fax:** +44 (0)1707 393909

www.vega-group.com

VEGA

serco

TABLE OF CONTENTS

1. INTRODUCTION	
1.1	PURPOSE AND SCOPE..... 4
2. LEVEL 1B	
2.1	NEW S-BAND WAVEFORM RECONSTRUCTION ALGORITHM ON RA-2 LEVEL 1B DATA..... 5
2.2	NEW USO CORRECTION ALGORITHM ON RA-2 LEVEL 1B DATA 5
2.3	OTHER CHANGES ON LEVEL 1B ADFs 6
3. LEVEL 2	
3.1	UPDATED RAIN FLAG ALGORITHM 7
3.2	NEW SEA-ICE FLAG ALGORITHM 7
3.3	OTHER CHANGES ON LEVEL 2 ADFs 7

AMENDMENT POLICY

This document shall be amended by releasing a new edition of the document in its entirety. The Amendment Record Sheet below records the history and issue status of this document.

AMENDMENT RECORD SHEET

ISSUE	DATE	DCI No	REASON
1.0	26 January 2010	N/A	First delivery

1. INTRODUCTION

1.1 Purpose and Scope

This document contains information to be distributed to the user community concerning the operational implementation of the RA2/MWR PF version 6.02L04 and CMA version 9.3 and reports on the ground processing evolutions included in this new release (See chapter 2)

The Envisat Altimetry products [Envisat Altimetry Data Set Version 2.0] issued from this new version of the ground processing are compliant with the RA2/MWR product specification Vol. 14 issue 4C available from the ESA URL http://earth.esa.int/pub/ESA_DOC/ENVISAT/Vol14_Ra2mwr_4C.pdf

Further details are provided in the Product Handbook (1.3), available at http://envisat.esa.int/pub/ESA_DOC/ENVISAT/RA2-MWR/PH_light_1rev3_ESA.pdf

2. LEVEL 1B

2.1 New S-Band Waveform Reconstruction algorithm on RA-2 Level 1b data

RA-2 sensor corrected anomaly:

An undesired behaviour of the S-band waveforms was encountered after launch and during the ENVISAT Commissioning phase: the waveforms are accumulated by the digital units of the RA-2 instrument with a random occurrence. The anomaly stops only when the RA-2 is set to stand-by. The new algorithm subtracts the accumulated waveforms, sample by sample, except for the first data block, when the previous sample is not available in the product.

Software evolution:

ADF modification: RA2_CON_AX: new parameter (S-Band_Threshold_Evaluation, Field #43) added in the AUX file.

L1b product impact: The content of the S-band waveform field (Field #18 in Main MDSR) will be modified in those cases where the S-band flag is TRUE (Field #14 Measurement Confidence Flag -bit 1 S-band anomaly flag).

Reference document: A. Martini, P. Femenias, G. Alberti, M.P. Milagro-Perez, RA-2 S-Band Anomaly: Detection and Waveform Reconstruction. "15 Years of Progress in Radar Altimetry" Symposium, Venice (Italy) 13-18 March 2006.

2.2 New USO Correction algorithm on RA-2 Level 1b data

RA-2 sensor corrected anomaly:

For an unknown reason a change of behaviour of the Ultra Stable Oscillator (USO) clock frequency occurred randomly in the period 1st February 2006 – 23rd January 2008 . When the anomaly occurs, the USO period increases rapidly during several hours lasting from several days to several months. This change of frequency has a direct impact on the altimetric range measurement in both Ku and S bands. Translated into range, the anomaly consists in an oscillating signal with an orbital period and amplitude of 30cm around a 5.6m mean bias. Since January 2008 the USO period bias and orbital variations disappeared, coming back to the nominal behaviour. The reason remains unexplained as well.

Software evolution:

The method proposed for the USO anomaly correction is the one currently used to correct by the long term USO drift. The difference lies in the choice of the step value: for the USO long term drift is set to 86400 s (equivalent to 1 day), while the adequate value in order to see the orbital fluctuations in the USO period was 100 s. The choice of a step of 100 s is a good compromise between a good restitution of the short wave length, and a low noise level.

ADF modification:

RA2_CON_AX: 3 new parameters added to the AUX file:

Field #40: step,

Field #41: Smooth_factor, and

Field #42: USO_correction_switch.

L1b product modification: 4 new parameters added to the product:

Field #24: Rx_dist_c,

Field #25: Rx_dist_f,

Field #66: USO_clock_smooth,

Field #67: USO_correction_quality_flag.

Reference document: Y. Faugère, A. Ollivier, O. Z. Zanifé, R. Scharroo, A. Martini, M..Roca, P. Femenias, An operational Correction for the RA-2 Side A USO Anomaly: Method and Performances Assessment. *ENVISAT Symposium, Montreaux (Switzerland) 23-27 April 2007*

2.3 Other changes on Level 1b ADFs

Ground processing tuning:

RA2_CON_AX: updated the following parameters:

Field #8: Zero padding factor for PTR evaluation,

Fields #11,12,13, and 14: Minimum and Maximum value of length of the stack used for averaging the in-flight time delay calibration factor for Ku and S Band,

Fields #15 and 16: maximum time lag in SP multiples between two Ku/S PTR measurements.

MWR_SLT_AX: Updated the following parameters:

Fields #2 and 3: Transmission coefficients of the reflector for 23.8 and 36.5 GHz

Fields #21 and 22: Efficiency factor for satellite contribution on the secondary lobes for 23.8 and 36.5 GHz

MWR_CHD_AX: deactivated 36.5 GHz drift correction

RA2_CHD_AX: updated parameter:

Field #40: Factor for PTR width computation

3. LEVEL 2

3.1 Update of the Rain Flag algorithm

Algorithm updates description:

In the algorithm the coefficients and look-up tables have been updated, in order to set the value of the flag.

ADF modification: updated parameter:

RA2_SOI_AX: Field #11 Node 34: Rain Flag coefficient

L2 product impact: updated parameter:

Field #147: Altimeter Rain Flag

3.2 Inclusion of a Sea-Ice Flag algorithm

Algorithm Description:

The new Sea-Ice algorithm includes a 2-state sea ice flag (ice-free ocean and sea-ice) and 4 values indicating the membership of the pixel to each class (ice-free ocean, first-year ice, multi-year ice and wet ice). They are provided as percentages between 0 and 100 in the product.

ADF modification:

RA2_SOI_AX: Fields #72-82: New parameters for Sea-Ice Flag algorithm

L2 product impact: New fields added to the product

Field #149: Sea-Ice flag;

Fields #150-154: Membership of the pixel for each of the 4 classes.

3.3 Other changes on Level 2 ADFs

Other changes will include only ADF updates.

Updated wind tables

ADF modification: updated parameters **to be in line with ECMWF model (added 10 more values)**

RA2_SOI_AX: Field #3: Tabulated values of RA-2 windspeed

Evolution from FES2002 to FES2004: new Ocean Tide and Tidal Loading

ADF modification:

RA2_TLD_AX: Update of the tidal wave frequencies

RA2_OT2_AX: Update of the tidal wave frequencies

RA2_SOI_AX: Node A33 Field #16: Frequency of the solution 2 tidal wave number 1 to 29

L2 product impact: updated parameters:

Filed #102: Total geocentric ocean tide height (solution 2)

Field #104: Tidal loading height (solution 2)

Sea State Bias: updated tables

ADF modification:

RA2_SSB_AX: updated tables based on the analysis of more than 10 cycles of RA-2 GDR data for the two RA-2 Ku and S bands.