




Physical Principles and Methods of Remote Sensing



Methods of Image Classification

Dr. Claudia Künzer

German Remote Sensing Data Center, DFD German Aerospace Center, DLR email: claudia.kuenzer@dlr.de


fon: +49 – 8153 – 28-3280



Classification Approaches




§ Classification: grouping of elements according to common properties





Urban Mapping: Manila, Philippines, 1975 - 2010 4






Landsat TM TerraSAR-X



Land Use Change: Southeast Asia, Indonesia, Sumatra






§ Land use change from 1982 until 2005 in Sumatra, Indonesia



Vegetation Differentiation: Global Land Cover





23


No data



MODIS Land Cover Product Reliability



Post classification change detection on the basis of MOD12Q1 land cover product







MODIS Land Cover Product Reliability



Slide courtesy of P. Leinenkugel




Stable	e Pixels 2001-2009	
Land Cover Type	Per Cent Land Cover Type F	Per Cent
Urban and built-up	98% Evergreen Needleleaf forest	22%
Evergreen Broadleaf forest	80% Mixed forest	17%
Water	64% Closed shrublands	12%
Grasslands	63% Barren or sparsely vegetated	2%
Woody savannas	38% Open shrublands	1%
Cropland/Natural vegetation mosaic	34% Deciduous Needleleaf forest	0%
Permanent wetlands	33% Deciduous Broadleaf forest	0%
Snow and ice	24% Savannas	0%
Croplands	23%	





Comparison of Global Landcover Products








Comparison of Global Landcover Products



Table 1. Generalized land cover legend for map comparison in West Africa including labels of the Land Cover Classification System (LCCS).


Generalized class	LCCS Label
evergreen broadleaf trees	A12-A3.A20.B2.XX.D1.E1 and A12-A3.A10.B2.XX.D1.E1 and A24-A3.A20.B2.XX.D1.E1
decidous broadleaf trees	A12-A3.A20.B2.XX.D1.E2 and A12-A3.A10.B2.XX.D1.E2
mixed/other trees	A12-A3.A20.B2 and A24-A3.A20.B2
shrubs	A12-A4.A20.B3
herbaceous vegetation	A12-A2.A20.B4
cultivated and managed vegetation/ agriculture (incl. mixtures)	A11 and A23
other shrub/herbaceous vegetation	A24-A2 and A24-A4
urban/built up	B15
barren	B16 and A12-A1.A14 and A12-A2.A14
water	B27-A1 and B28-A1





MODIS Cloud Mask Comparison









The Vegetation Model BETHY/DLR















My first Classifications, Xinjiang, China (2000)






















1D-Classification (e.g. LST Intervals)





Histogram of the data set




Grey value transfer function (Class code)



Classification Approaches






© ERDAS 1997

sposition of two pixel clouds in a two dimensional feature space



Spectral Seperability








Signature Analysis of the Histogram



§ Illustrates the distribution of signatures



§ Shows possible confusion in signatures







- § Supervised: interactive
- § The supervised classification is based on utilising known training areas for classification
- § The user **defines training areas** for each class in the **satellite image** and the classification algorithm searches for further pixels with similar properties (statistical analysis of the entire scene)
- § The spectral properties of each class are derived from the regional mean values of the training areas and the respective covariance
- § Result: homogeneous classes with explicit labels
- § E.g. box -, parallelepiped -, minimum distance -, spectral angle mapper -, maximum likelihood classification



§ Characteristic properties of the class Oi are

Mean value

$$\overline{g}_{k}^{i} = \frac{1}{N} \sum_{l=1}^{N} g_{k,l}^{i}$$
 $k = 1, K$ $i = 1, I$

k ... Band index

N ... Number of pixel in the training area

i ... Class index


- Standard deviation (for individual bands) or variance-covariance function

$$\mathbf{s}_{k}^{i} = \sqrt{\frac{\mathbf{\hat{o}}_{k}^{N} \left(g_{k,l}^{i} - \overline{g}_{k}^{i}\right)^{2}}{N-1}} \qquad k = 1, K$$

$$i = 1, I$$







(1) TRAINING STAGE
Collect numerical
data from training
areas on spectral
response patterns
of land cover
categories

(2) CLASSIFICATION STAGE Compare each unknown pixel to spectral patterns; assign to most similar category (3) OUTPUT STAGE
Present results:
maps
tables of area data
digital data files

© Lillesand 1978





- § Unsupervised: without user interaction
- § Purely mathematical, statistical analysis of spectral bands
- § Cluster analysis for the determination of discriminable classes in a defined **n-dimensional feature space** (n = number of bands)
- § Purely mathematical approach; no semantics, meaning of the features has no relevance
- § Algorithm groups image pixels into clusters (grouping is based on statistical properties)
- § Result: homogenous classes without any thematic connotation
- § The thematic meaning of each cluster has to be assigned by the user in a further step (class assignment)
- § e.g. *isodata* algorithm, *k-means* algorithm





Unsupervised classification	Supervised classification
Computational intensive, adequate for quick 'snapshot': which classes are spectrally well discriminable?	Computational less intensive
Previous knowledge not required (but desirable!)	Knowledge on study area should exist (ground truth, GPS)
Definition of number of classes is critical: If to high – classes not discriminable, if to low – unnecessary merging of classes	Selection of training areas critical: risk of being not representative, not enough, extreme overlap of classes in the feature space
Results are objective (class assignment subjective!)	Results depend on selected training areas selected by the user
Applicable to arbitrary data sets; however, class assignment individually for each data set!	For each new EO-data: possibly new training sites necessary (illumination- and atmospheric conditions, land cover dynamics)
,New', unknown classes in the study area can be identified	Only already defined classes (based on training sites) can be identified
Accuracy often insufficient	Approved method
Both approaches can be performed with prevalent remote sensing software packages	





Unsupervised classification	Supervised classification
Computational intensive, adequate for quick 'snapshot': which classes are spectrally well discriminable?	Computational less intensive
Previous knowledge not required (but desirable!)	Knowledge about study area should be existent (ground truth, GPS)
Definition of number of classes is critical: If to high – classes not discriminable, if to low – unnecessary merging of classes	Selection of training areas critical: risk of being not representative, not enough, extreme overlap of classes in the feature space
Results are objective (class assignment subjective!)	Results depend on selected training areas selected by the user
Applicable to arbitrary data sets; however, class assignment individually for each data set!	For each new EO-data: possibly new training sites necessary (illumination- and atmospheric conditions, land cover dynamics)
,New', unknown classes in the study area can be identified	Only already defined classes (based on training sites) can be identified
Accuracy often insufficient	Approved method

Both approaches can be performed with prevalent remote sensing software packages





Unsupervised classification	Supervised classification
Computational intensive, adequate for quick 'snapshot': which classes are spectrally well discriminable?	Computational less intensive
Previous knowledge not required (but desirable!)	Knowledge about study area should be existent (ground truth, GPS)
Definition of number of classes is critical: If to high – classes not discriminable, if to low – unnecessary merging of classes	Selection of training areas critical: risk of being not representative, not enough, extreme overlap of classes in the feature space
Results are objective (class assignment subjective!)	Results depend on selected training areas selected by the user
Applicable to arbitrary data sets; however, class assignment individually for each data set!	For each new EO-data: possibly new training sites necessary (illumination- and atmospheric conditions, land cover dynamics)
,New', unknown classes in the study area can be identified	Only already defined classes (based on training sites) can be identified
Accuracy often insufficient	Approved method

Both approaches can be performed with prevalent remote sensing software packages





Unsupervised classification	Supervised classification
Computational intensive, adequate for quick 'snapshot': which classes are spectrally well discriminable?	Computational less intensive
Previous knowledge not required (but desirable!)	Knowledge about study area should be existent (ground truth, GPS)
Definition of number of classes is critical: If to high – classes not discriminable, if to low – unnecessary merging of classes	Selection of training areas critical: risk of being not representative, not enough, extreme overlap of classes in the feature space
Results are objective (class assignment subjective!)	Results depend on selected training areas selected by the user
Applicable to arbitrary data sets; however, class assignment individually for each data set!	For each new EO-data: possibly new training sites necessary (illumination- and atmospheric conditions, land cover dynamics)
,New', unknown classes in the study area can be identified	Only already defined classes (based on training sites) can be identified
Accuracy often insufficient	Approved method
Both approaches can be performed with prevalent remote sensing software packages	





Unsupervised classification	Supervised classification
Computational intensive, adequate for quick 'snapshot': which classes are spectrally well discriminable?	Computational less intensive
Previous knowledge not required (but desirable!)	Knowledge about study area should be existent (ground truth, GPS)
Definition of number of classes is critical: If to high – classes not discriminable, if to low – unnecessary merging of classes	Selection of training areas critical: risk of being not representative, not enough, extreme overlap of classes in the feature space
Results are objective (class assignment subjective!)	Results depend on selected training areas selected by the user
Applicable to arbitrary data sets; however, class assignment individually for each data set!	For each new EO-data: possibly new training sites necessary (illumination- and atmospheric conditions, land cover dynamics)
,New', unknown classes in the study area can be identified	Only already defined classes (based on training sites) can be identified
Accuracy often insufficient	Approved method
Both approaches can be performed with prevalent remote sensing software packages	





Unsupervised classification	Supervised classification
Computational intensive, adequate for quick 'snapshot': which classes are spectrally well discriminable?	Computational less intensive
Previous knowledge not required (but desirable!)	Knowledge about study area should be existent (ground truth, GPS)
Definition of number of classes is critical: If to high – classes not discriminable, if to low – unnecessary merging of classes	Selection of training areas critical: risk of being not representative, not enough, extreme overlap of classes in the feature space
Results are objective (class assignment subjective!)	Results depend on selected training areas selected by the user
Applicable to arbitrary data sets; however, class assignment individually for each data set!	For each new EO-data: possibly new training sites necessary (illumination- and atmospheric conditions, land cover dynamics)
,New', unknown classes in the study area can be identified	Only already defined classes (based on training sites) can be identified
Accuracy often insufficient	Approved method
Both approaches can be performed with prevalent remote sensing software packages	





Unsupervised classification	Supervised classification
Computational intensive, adequate for quick 'snapshot': which classes are spectrally well discriminable?	Computational less intensive
Previous knowledge not required (but desirable!)	Knowledge about study area should be existent (ground truth, GPS)
Definition of number of classes is critical: If to high – classes not discriminable, if to low – unnecessary merging of classes	Selection of training areas critical: risk of being not representative, not enough, extreme overlap of classes in the feature space
Results are objective (class assignment subjective!)	Results depend on selected training areas selected by the user
Applicable to arbitrary data sets; however, class assignment individually for each data set!	For each new EO-data: possibly new training sites necessary (illumination- and atmospheric conditions, land cover dynamics)
,New', unknown classes in the study area can be identified	Only already defined classes (based on training sites) can be identified
Accuracy often insufficient	Approved method

Both approaches can be performed with prevalent remote sensing software packages



Unsupervised classification: isodata (I)




- § Iterative algorithm
- § Divides pixels successively into subpopulations (clusters)
- § Iterative grouping into clusters is determined according to spectral distance to the clusters' mean value
- § Each pixel is iteratively assigned to the class with the shortest spectral distance to the class centre point
- § Input parameters by the user: number of clusters, number of iterations, termination condition



Unsupervised classification: isodata (II)



The ISODATA algorithm uses the minimum spectral distance formula to form clusters. After the initial clusters are formed the process repeats itself, locating new means. These new means are then used in the next iteration, and the next until either the maximum number of iterations has been performed OR the maximum percentage of unchanged pixel assignments has been reached.





Unsupervised Classification





Disadvantage

- § Computational intensive
- § Accuracy often insufficient



Advantage


- § adequate for quick 'snapshot': which classes are spectrally well discriminable?
- § ,New', unknown classes in the study area can be identified
- § Previous knowledge not required
- § Results objective, only spectral properties are assessed
- § Standard method, implemented in all remote sensing software packages



Supervised Classification



- § User defines several training sites (TS) for each class
- § The more heterogeneous the class, the more TS required
- § TS should be as homogenous as possible
- § Selection of TS should be evenly distributed over the entire image
- § TS also usable as cluster centres
- § Numerous ,supervised ' classification algorithms e.g. MinDist, MaxLikeli,...






Supervised: Parallel Piped classification (I)



- S Determination of multidimensional 'boxes' around the class centre points (in consideration of the standard deviation)
- § Uses Euclidian distance
- § Considers statistics (calculation of standard deviation for each band)



Band 4 digital number -----

© Lillesand 1978




Supervised: Parallel Piped Classification (II)



§ Distinctive feature:

- Box surrounding mean value with extent of h-fold standard deviation
- **§** Consideration of variance
- § May generate overlapping classes in the feature space
- § Class membership of each pixel is assessed






Supervised: Parallel Piped classifikation (IV)



- § ,Parallel piped' classification of Cairo based on Landsat TM
- § Pseudo colour TM7, 5, 2 und 4, 2, 1








Supervised: Minimum distance classification (I)



- Minimum distance to mean values
- **Class representation:**

$$\overline{\mathbf{g}}^{\mathbf{i}} = \left(\overline{g}_1^i \dots \overline{g}_k^i \dots \overline{g}_K^i\right)^T$$

- Class assignment
 - Each pixel is assigned to the class with the minimum distance to the class' mean value in the feature space
- Discriminator
 - in 2D-space: perpendicular bisector
 - in nD-space: Hyper-plane





Supervised: Minimum distance classification (II)



§ Calculation of Euclidian g_2 distance between pixel U and centre points O^i :

$$d = \sqrt{(\mathbf{g} - \overline{\mathbf{g}}^i)^T (\mathbf{g} - \overline{\mathbf{g}}^i)}$$

$$d^2 = (\mathbf{g} - \overline{\mathbf{g}}^i)^T (\mathbf{g} - \overline{\mathbf{g}}^i)$$


$$150 - \mathbf{g}^i$$

§ Advantage

- Easy calculation
- In order to avoid misinterpretations: small assignment radii

§ Disadvantage


- Inadequate statistical rationale
- Does not account for range of dispersion





Supervised: Minimum distance classification (II)






Band 4 digital number



Supervised: Minimum distance classification (III)



- § Example for "unjustified" assignment
 - Class 1: homogeneous (e.g. water surface)
 - Class 2: heterogeneous class (e.g. settlement)
 - Pixel close to the perpendicular bisector may be assigned to the homogenous class, although membership to the inhomogeneous class is more probable






Supervised: Spectral Angle Mapper (SAM) (I)



- § The **SAM-Method** is based on the estimation of the spectral similarity in the (n-dimensional) feature space
- § Signature is described by a vector, starting at the coordinate system's origin
- § Length of the vector resembles reflection intensity
- § Difference between spectra is described by the angle
- § By assessing the angle difference between pixel and reference spectrum an image can be divided in any number of classes





Supervised: Spectral Angle Mapper (SAM) (II)



Calculation of angle α is based on trigonometric function of the arc cosine, for which for all bands *nb*, all angles between the sum of all target pixels t, and all reference pixels r is calculated

$$\alpha = \cos^{-1}\left(\frac{\sum\limits_{i=1}^{nb}t_{i}r_{i}}{\left(\sum\limits_{i=1}^{nb}t_{i}^{2}\right)^{1/2}\left(\sum\limits_{i=1}^{nb}r_{i}^{2}\right)^{1/2}}\right) \quad \alpha = \text{spectral angle between vectors nb} = \text{number of spectral bands} \quad t = \text{target pixel} \quad r = \text{reference pixel}$$

- A pixel is assigned to the class whose spectrum has the smallest angle with the respective pixel
- § Size of the angle in radiant
- Angle is assessed, not the length of the vector!




Supervised: Spectral Angle Mapper (SAM) (III)



§ Advantage

- Fast and easy approach
- Comprehensible for the user
- Relative robust against
 Illumination differences
 (topography, light source, sensor, etc.)
- Comparability of image spectra with lab spectra



§ Disadvantage

- Illumination tolerance is accompanied by insensitivity for detecting certain physiologic changes
- Similar spectra, which only significantly differ in their albedo (e.g. needle leaf and broad leaf forests), are wrongly classified



Statistical Basics



Mean value:

$$\overline{g}_k = \frac{1}{N} \sum_{l=1}^{N} g_{k,l} \qquad k = 1, K$$

$$\overline{\mathbf{g}} = (\overline{g}_1 \dots \overline{g}_k \dots \overline{g}_K)^T$$

Variance-Covariance-Matrix:



$$\mathbf{C} = \overset{\mathbf{c}}{\mathbf{c}} \overset{2}{\mathbf{c}} \qquad \qquad \mathbf{S}_{1K} \overset{\mathbf{\ddot{o}}}{\dot{\mathbf{c}}}$$

$$\mathbf{C} = \overset{2}{\mathbf{c}} \overset{\mathbf{M}}{\mathbf{M}} \qquad \qquad \mathbf{S}_{1K} \overset{\mathbf{\ddot{o}}}{\dot{\mathbf{c}}}$$

$$\overset{\mathbf{c}}{\mathbf{c}} \boldsymbol{s}_{K1} \qquad \qquad \mathbf{L} \qquad \boldsymbol{s}_{K} \overset{2}{\dot{\mathbf{c}}} \overset{\mathbf{\dot{c}}}{\dot{\mathbf{c}}}$$

Matrix diagonal: variances of the single variables

Other fields: co-variances between the image bands

Variance = square of standard deviation:

$$s_k^2 = \frac{1}{N-1} \sum_{l=1}^{N} (g_{k,l} - \overline{g}_k)^2$$
 $k = 1, K$

Covariance (for multiple variables):

Measure for correlation between two or more variables

$$\boldsymbol{s}_{ij}^{2} = \frac{1}{N-1} \sum_{l=1}^{N} \left(g_{i,l} - \overline{g}_{i} \right) \left(g_{j,l} - \overline{g}_{j} \right) \qquad i, j = 1, K$$
variable 1 variable 2




Statistical Basics - Probability Density




$$f_{\mathbf{g}_{2}}^{\mathbf{g}_{1}} = \frac{1}{2\rho\sqrt{s_{1}^{2}s_{2}^{2} - s_{12}^{2}}} \exp_{\mathbf{g}_{1}}^{\mathbf{g}_{2}} + \frac{s_{1}^{2}s_{2}^{2}}{2\left(s_{1}^{2}s_{2}^{2} - s_{12}^{2}\right)} \underbrace{\mathbf{g}_{\mathbf{g}_{1}}^{\mathbf{g}_{1}} - \mathbf{g}_{1}^{\mathbf{g}_{1}}}^{\mathbf{g}_{1}} - 2s_{12} \frac{(g_{1} - \overline{g}_{1})(g_{2} - \overline{g}_{2})}{s_{1}^{2}s_{2}^{2}} + \frac{(g_{2} - \overline{g}_{2})^{2}}{s_{2}^{2}} \underbrace{\mathbf{g}_{2}^{\mathbf{g}_{1}} - \mathbf{g}_{2}^{\mathbf{g}_{1}}}^{\mathbf{g}_{1}} + \frac{(g_{2} - \overline{g}_{2})^{2}}{s_{1}^{2}s_{2}^{2}} + \frac{(g_{2} - \overline{g}_{2})^{2}}{s_{2}^{2}} \underbrace{\mathbf{g}_{2}^{\mathbf{g}_{1}} - \mathbf{g}_{2}^{\mathbf{g}_{1}}}^{\mathbf{g}_{1}} + \frac{(g_{2} - \overline{g}_{2})^{2}}{s_{2}^{2}} \underbrace{\mathbf{g}_{2}^{\mathbf{g}_{1}} - \mathbf{g}_{2}^{\mathbf{g}_{2}}}^{\mathbf{g}_{2}} + \frac{(g_{2} - \overline{g}_{2})^{2}}{s_{2}^{2}} \underbrace{\mathbf{g}_{2}^{\mathbf{g}_{1}} - \mathbf{g}_{2}^{\mathbf{g}_{2}}}^{\mathbf{g}_{2}} \underbrace{\mathbf{g}_{2}^{\mathbf{g}_{1}} - \mathbf{g}_{2}^{\mathbf{g}_{2}}}^{\mathbf{g}_{2}} + \frac{(g_{2} - \overline{g}_{2})^{2}}{s_{2}^{2}} \underbrace{\mathbf{g}_{2}^{\mathbf{g}_{2}} + \frac{(g_{2} - \overline{g}_{2})^{2}}{s_{2}^{2}}}^{\mathbf{g}_{2}} \underbrace{\mathbf{g}_{2}^{\mathbf{g}_{2}} + \frac{(g_{2} - \overline{g}_{2})^{2}}{s_{2}^{2}}}^{\mathbf{g}_{2}^{\mathbf{g}_{2}}} \underbrace{\mathbf{g}_{2}^{\mathbf{g}_{2}} + \frac{(g_{2} - \overline{g}_{2})^{2}}{s_{2}^{2}}}^{\mathbf{g}_{2}^{\mathbf{g}_{2}}}^{\mathbf{g}_{2}^{\mathbf{g}_{2}}}^{\mathbf{g}_{2}^{\mathbf{g}_{2}}}^{\mathbf{g}_{2}^{\mathbf{g}_{2}}}^{\mathbf{g}_{2}^{\mathbf{g}_{2}}}^{\mathbf{g}_{2}^{\mathbf{g}_{2}}}^{\mathbf{g}_{2}^{\mathbf{g}_{2}}^{\mathbf{g}_{2}}^{\mathbf{g}_{2}^{\mathbf{g}_{2}}}^{\mathbf{g}_{2}^{\mathbf{g}_{2}}}^{\mathbf{g}_{2}^{\mathbf{g}_{2}}^{\mathbf{g}_{2}}^{\mathbf{g}_{2}^{\mathbf{g}_{2$$

Lines of similar probability densities in **2D-case ellipse**




Porbability density function 3D case



Supervised: Maximum Likelihood Classification (I)




- § Is based on k-dimensional normal distribution
- § Class membership is based on highest probability density
- § Discriminator:
 - Isolines with equal probability density between the respective classes





Supervised: Maximum Likelihood classification (III)





- § Probability density function calculated on the basis of mean vector and covariance matrix
- § Vertical axis: probability of class membership
- § Each spectral class has a probability density function (bell shaped) of class membership




Supervised: Parallel Piped classification (IV)



§ Maximum Likelihood Classification of Cairo City based on Landsat TM

§ Pseudo colour TM 7, 5, 2 und 4, 2, 1







Supervised: Support Vector Machines (I)



- § Support Vector Machines (SVM)
- § Large margin classifier
- § Groups a population within an d-dimensional feature space in classes so that the margin between the classes is maximised

Starting position

- n training data (x₁ y₁), (x₂ y₂), ..., (x_n y_n)
- with $x_i \in R_a$
- and $y_i \in \{-1, +1\}$ (i=1,2,...N)

§ Geometrical approach


- Group samples in the feature space into two classes using a hyperplane



Supervised: Support Vector Machines (II)



§ Optimisation problem: Maximising distance between classes and hyper plane






Supervised: Support Vector Machines (III)



- § Also in n-dimensional feature space applicable
- § Also for non-linear discriminable classes applicable






Supervised: Support Vector Machines (IV)



§ Popularity of SVMs in remote sensing analyses within the last decade





Supervised: Support Vector Machines (V)





Disadvantage

- § New training data required for each input data set (even after e.g. atmospheric correction differences in class variance
- § Non-linear discriminable data require additional computing time




Advantage

- § Little computational costs (based only on a few support vectors)
- § Good generalisation (performs well for heterogonous classes)
- § Good results with only a small number of training data
- § works well also with high number of dimensions (multi/hyperspectral)



Supervise Classification: Decision Trees (I)





- § Many global land cover classifications
- § Friedl & Brodley, Hansen et al., Cihlar et al., Wen & Tateishi, ...
- § Well suited for differentiation of vegetation types
- § Often used for local surface extraction (cloud, snow, ice ...)
- § Terms: Root, Branches, Nodes, Leaf



Supervised: *Decision trees* (III)





Disadvantage

- § A-priori knowledge required
- § Construction of tree is labour- and time-intensive
- § Decision rules are only transferable with limitations (variation in time and space)



Advantage

- § Quite flexible and versatile applicable
- § Standardised and comparable results
- § Only little additional efforts once the decision tree is constructed
- § very focused with respect to band and feature selection
- § decisions are based on physical properties
- § extendable and transferable (with certain efforts for adaptation)
- § Only little previous knowledge required to apply existing tree
- § reasonable for large areas
- § Implemented in all commercial remote sensing software packages



Supervised: Object-oriented classification (I)




Fields of application


- § High resolution data (Airborne, IKONOS, QuickBird, ETM+, ASTER)
- § Complex land use classes (Urban areas, commercial areas, road networks,...especially images with 'structures')
- § Detailed land use and vegetation classification
- § Software: eCognition (Definiens Developer)



Satellite Image



object-oriented result



pixel based result




Supervised: Object-oriented classification (II)





Segmentation

Object DB



ID	Meandiff.t	Shapeindex	Prozentual
3	29,61	1,12	0,00
6	14,46	2,37	59,48
11	12,31	1,54	70,13
22	8,19	1,13	100,00
32	-14,62	1,20	9,52
35	9,37	1,46	65,22
36	-19,63	1,44	14,81
42	10,30	1,61	89,47
3 9	11,92	1,59	100,00
73	13,95	1,90	48,00
79	27,98	1,70	14,29
85	12,12	1,51	67,86
137	18,88	1,06	50,00
149	8,41	1,33	100,00
181	9,83	1,24	62,50
198	11.43	1,58	90,00

IKONOS 08/2001


Segments
© Mott, TU München 2003



Supervised: Object-oriented classification (III)




Segmentation: the scale-parameter





Supervised: Object-oriented classification (IV)








Supervised: Object-oriented classification (IV)








Supervised: Object-oriented Classification (IV)








Supervised: Object-oriented classification (V)



- § Construction of a semantic network
- § Objects of various scale levels are interconnected




"Bottom up region merging technique" starts on the 1-pixel-object level. The objects that are created on different scales are connected by a hierarchical network.



Supervised: Object-oriented classification (VI)



§ Object features




(A)original image IKONOS 8/2001, (B) mean, (C) standard deviation, (D) ,compactness'



Supervised: Object-oriented classification (VII)




§ Construction of class descriptions via fuzzy-membership curves for significant object features





Supervised: Object-oriented classification (VII) Example Osterseen





Area wide classification

wetland

LW - meadow

LW - maize

LW – grass land typ 1

LW – grass land typ 2

Needle-leaved forest

Broad-leaved forest

Settlement/ impervious surface

Water surface

" Distinctive land cover classes in ArcView-Shape format

Classification by NSG/FFH

IKONOS 08/2001








Supervised: Object-oriented classification (VII) Example Osterseen




§ Quantitative statements possible





Supervised Classification: Object-oriented classification (VIII)





"Relationships between adjacent objects!




Landscape elements can be detected automatically



Supervised Classification: object-oriented classification (IX) Example Mekong Delta








Supervised Classification: object-oriented classification (IX) Example Mekong Delta



TerraSAR-X Stripmap HH mosaic

(31.12.2009; 13.02.2010; 24.02.2010)






Supervised Classification: object-oriented classification (IX) Example Mekong Delta



Watermask from TerraSAR-X mosaic






Supervised Classification: object-based classification (IX) Example Mekong Delta










Supervised Classification: object-oriented classification (IX) Example Mekong Delta




Mangrove Map for Ca Mau Province, Mekong Delta, Vietnam. 2010.





Supervised Classification: object-oriented classification (IX) Example Mekong Delta







Supervised: Object-oriented classification (IX)






Disadvantages

- Only few, relatively expensive(!) software solutions (dongle)
- Iterative, very(!) time consuming process
- Quality highly dependent on competence of user
- Rule set often only partly transferable
- Ok for smaller areas, but not so much for mass data throughput



Advantages

- Very high accuracies can be obtained
- Direct post-processing in GIS
- Fuzzy logic rationale applicable
- Additional object features (beside spectral information) can be used for classification
- Very useful if spectral variance within a class is higher then spectral variance between classes (e.g. urban)







How much is too much???





Do you really want to see every single car?

Too much information also creates confusion.

300 channels are usually not more useful than 150. The same might apply for spatial resolution: at one point its all too much.







There are 2 essential questions you need to ask for each classification:

1. How accurate is the classification?

2. How was the accuracy recorded?

If these questions are not answered adequately, then there is reasonable doubt ...



Validation: Indirect validation – reference data with a higher resolution



- § Different users have different demands for accuracy assessment
- § Proper registration of the data
- § Errors in the basis for comparison are propagated
- **§** Reference maps
 - Often not up to date
 - Accuracy unknown
 - Different classification scheme

§ Field campaign

- Time of recording?
- Expensive
- Field data is also a type of classification

§ Data with higher resolution

- Time of recording?
- Are the classes clearly detectable?
- Spectral resolution (Landsat 7 bands IKONOS 4 bands)



Validation: Ground Control Points - GCPs




- § GCPs are **control points** or sample points
 - GPS points, which classes were collected in a field survey
 - Sample points, which are chosen on the record of this data set or another data set (larger scale: aerial photography, high resolution data)
 - Selection of sample points in the image and subsequent field survey (if possible) = **ground truthing**
- § For each control point the "true" class is determined
- § Accuracy assessment means: Comparison of the classification with the assigned "true" class
- § Results will be shown and analysed in a confusion matrix



Validation: User and Producer Accuracy








Validation: User Accuracy








Validation: Producer Accuracy








Validation / Classification Accuracy: Producer vs. User Accuracy



E.g.: Class "Forest"



How many % of the training area were correctly classified

Probability, that a pixel, assigned to this class, really belongs to that class



Validation: Confusion Matrix



Comparison of the target classes to the actual classes The reference pixel in the matrix

Referenzkl.	Klassifizierungergebnis						
	Klasse 1	Klasse 2		Klasse k	TOTAL		
Klasse 1							
Klasse 2							
Klasse k							
TOTAL							

Beispiel:


Referenzkl.	Klassifizierungergebnis					
	Wald	Stadt	Wiese	Industrie	TOTAL	
Wald	179	5	10	3	209	
Stadt	9	203	57	12	281	
Wiese	13	25	176	2	216	
Industrie	0	0	0	28	28	
TOTAL	201	233	243	45	722	



Validation: also ,Accuracy Assessment



Ground truth polygon that have been mapped during a field campaign





Validation: Indirect validation – reference data with a higher resolution



- § Aerial photographs or higher-resolution data are considered as a good basis for comparison (Congalton, 1991)
- § Assumption: Interpretation of the higher-resolution data is 100% correct (applies not always)
- § There are also existing land use maps for reference.
 Note: These maps are often not up to date and their accuracy is not well known



Validation: Exclusion of homogeneous classes



- § In order to prevent the "distortion" of the quality measure certain homogeneous or uninteresting classes are usually excluded from the validation
- § Depending on the problem, e.g.
 - Large bodies of water
 - Clouds and cloud shadows
 - Snow



Validation: Principles of sample design



Class definition

§ Reference data should be collected under the same assumptions and in the same class scheme (same classes and decision criteria), as the classification to be tested

Adequate spatial resolution –

§ Reference data should be collected in the same scale level (same MMU). The sample unit (e.g. pixels, pixel clusters, polygons) specifies the level of detail.

Sample number

§ At least ~ **50 Sample per class** it should be. When dealing with a very large study area (> 400,000 ha) or many classes (> 12) the sample number should be increased. (e.g. 75 – 100 per class). The sample number is to be adjusted, dependent on the importance of the class und the class-specific variability in the feature space.



Validation: Principles of sample design



Sampling plan

- § A stratified, randomly distributed sampling plan for each class is to be made. This ensures that all classes are examined.
- § The organization of a field campaign is to be conducted according to the classification.
- § When ground truth data are collected at the beginning of a project it is recommended to distribute the samples randomly. Important is the logical distinction between training and reference areas.

Summarized from Congalton and Green 1999



Spectral Unmixing (I)



§ Also known as

- Spectral Mixture Analysis
- Sub Pixel Classification


§ Idea:


- The majority of the pixels measure the reflectance of more than one "pure" object class ("mixed pixels")
- Multispectral data of one pixel include depending on the area fraction – a weighted average of the reflectance's of the participating object classes
- The task of the "unmixing" is to determine the area fraction of each pixel
- The sub-pixel classification does not determine the sub-pixel location of the classes, but only the portion



UNIVERSITÄT Spectral Unmixing (II) - mostly for hyper spectral data 4










Spectral unmixing (III)



- § Pixel spectrum is rarely ,pure*
- § E. g. mixed pixels from two or more object classes (50:50 mixture of "parking" and "vegetation" edge pixels of a parking lot)
- § Classes to be segregates are so-called "endmembers"







Spectral Unmixing (IV)



§ Example



As a result of the unmixing process of the multispectral input image a so-called fraction-(endmember)-image is produced. The number of spectral bands of the new image are corresponding to a maximum of those of the original.




Red Fraction Image


Green Fraction Image



Spectral Unmixing (V)







© Künzer 2005

where.

A m in-matrix of spectral endmembers (spectral library) in n spectral bands

 $X = A^{-1} \cdot R$

© Fisher 1997

X: vector of unknown abundances of the endmembers

R: measured reflection of the image pixel

 $A \cdot X = R$

$$R_{j} = \sum_{j=1}^{n} f_{j} \times RE_{ij} + \sigma_{j} \quad and \quad \sum_{j=1}^{n} f_{j} = 1$$

and

where.

R : spectral reflectance of a mixed spectrum in image band i

f: fraction of each endmember j calculated band by band

 $RE_{\mathbb{Z}}$ reflectance at the endmember spectrum $\mathfrak z$ in band $\mathfrak z$


7, band number

f: each of the n image endmembers

 f_0 residual error or the difference between the measured and the modeled DN in band i

vermodeling error in band i

n number of endmembers



Result of *unmixing* of Landsat TM in area of Wudan, China. Brightness: 'coal'-share

94



Spectral Unmixing (VI)



§ Theory of linear unmixing:

$$g'_i = \sum_{e=1}^{N} g_{i,e} f_e + e_i$$
 $i = 1, k$ k=number of bands

- $g_{i,e}$ known grey values of the e-th endmember in the i-th band
- g'_i Grey value of a pixel in the i-th band
- f_e Fraction components (=unknown), noise!
- E_i Error term (=improvement in the sense of adjustment)

ð It can not be determined more fraction components than error equations can be set up, i.e. not more than bands than are available in the original image.



Spectral Unmixing (VII)



§ First step:

- Search for "pure" endmembers in the original image (i.e. spectrally distinct classes that do not consist of mixed pixels)
- Extracting the spectral features of these endmembers
- Pixel Purity Index Calculations (PPI)

§ Second step:

- Setting up a system of equations
- Solved by the method of least squares

§ Third step:

- The found endmember components are sequentially multiplied by all pixels
- Result: **fraction images** in relation to the selected endmembers



Spectral Unmixing (VIII)




4 Endmember


A: Coal


B: Desert sand


C: Arkose Sandstone

D: Vegetation












Spectral Unmixing (IX) – Endmember search






Field measurements with a spectroscope

Laboratory spectra



2.0

© DLR





Spectral Unmixing (X)





Advantages:

- Physical method of this method
- Objective method without subjective influence of the producer
- Quantitative results on sub-pixel basis
- Also detected objects that are not perceived visually
- Especially suitable for chemical, geological and mineralogical investigations
- Not only for hyper spectral data



Disadvantages:

- Pre-processing of the images and spectra is very complex
- Can be performed only by experts
- Difficult in topographically heterogeneous areas (DTM Quality!)
- Minimum number of recording channels is required!
- Software packages with programming interface are needed (e.g. ENVI(IDL, C))



Spectral Feature Fitting (SFF) (I)



§ Aim

- Comparison of the pixel spectrum with a reference spectrum

§ Method


- Based on ,least squares best-fit' approach: ,The better the fit, the smaller the sum of the squared distances between the two spectra compared'
 - The measure for this is the *Root Mean Square Error* (RMS)
 - It will be generated a corresponding RMS-image
 - The RMS-image shows which are similar to the selected endmember spectrum
 - Or comparison of the input data set with the complete spectra database O
 - The comparison of the spectra is only useful if the "Continuum" has been removed.



Spectral Feature Fitting (SFF) (II)



§ A "continuum" for each input spectrum is defined (local maxima are determined and connected linearly)






Spectral Feature Fitting (SFF) (III)



§ Minima of the corrected spectrum are determined




The 10 strongest absorption regions per spectrum are determined



Spectral Feature Fitting (SFF) (IV)



- Wavelength, position, depth, width at half maximum depth (full width at half the maximum depth (FWHM)) and asymmetry for all 10 distinct absorption regions are determined and listed in a table
- § Comparison with reference spectrum





Spectral Feature Fitting (SFF) (VI)





Advantages:

- Has proven particularly useful in geology
- Effective in the search of "known" objects/materials
- Useful method for the incorporation of the spectral databases and spectrometer measurements in the study
- Physical background of the method
- Objective method without subjective influence of the producer
- Not only for hyper spectral data



Disadvantages:


- Very laborious and time consuming (PhD thesis?)
- Pre-processing of the images and spectra is very complex
- Can be performed only by experts
- Difficult in topographically heterogeneous areas (DTM Quality!)
- Minimum number of recording channels is required!
- Software packages with programming interface are needed (e.g. ENVI(IDL, C))



Automated tool TWOPAC



TWOPAC – Twinned object and pixel-based automated classification chain



Standardized interface for process controlOGC Web Processing Services (WPS) –

automated




Input Data





utomated







DATA

Input Data ('Stack' Generation)





§ Rather mean values with guaranteed stability than single values (transfer and comparability)



PRE-PROCESSING


Correlation
matrix between
variables, layer
with too high
correlation
indices to be
eliminated
(e.g. NDVI full
year max. and
NDVI summer
max.)
Layer Stack: > 50



Input Data ('Stack' Generation)



- § MODIS (NIR, RED, NDVI, 250m)
- § SRTM (height, slope, exposition, 250m)






Definition of the Classification Scheme



manual

automated




§ Based on the standards of the Land Cover Classification System (LCCS)



Definition of the Classification Scheme









Training and validation "samples"





Landsat scenes: evenly distributed, segmented, trained; Same year as MODIS (spring and fall to collect phenological differences)






Training Data Management





automated



§ sample Database
(PostgreSQL with PostGIS)




Classification



manual

automated



§ Classification methods:

- Support Vector Machine
- Maximum Likelihood
- C5.0 Rulesets (Decision Tree)



C5-based Creation of a Decision Tree



Rules:

```
Rule 1: (1067/1, lift 6.4)
   ndvi_mi_su > 635
   ndvi_r_su <= 626
   ndvi_m_ws <= 817
   red_m_aw > 1239
   nir_m_su <= 2624
   nir_ma_ws > 2183
   nir_m_ws <= 4342
   -> class 17 [0.998]
```

```
Rule 2: (501, lift 6.4)
   ndvi_ma_su <= 1608
   red_r_aw > 4280
   nir_ma_su > 1728
   nir_r_su > -25575
   nir_m_ws <= 2550
   -> class 17 [0.998]
```

```
Rule 3: (404, lift 6.4)

ndvi_mi_yr > -871

ndvi_m_yr > 1822

ndvi_r_yr > 3951

ndvi_ma_aw <= 2306

ndvi_m_ws <= -217

red_mi_aw <= 841

nir_ma_aw > 5298


-> class 17 [0.998]
```

- § C5: freely available software that performs a discriminant analysis to separate the variables
- § Originally not created for image processing, but you can use it for that
- § Output for the separability of the classes (derived from the training data) is an ASCII text file
- § Python script transfers the ASCII file automatically into an applicable decision tree



TWOPAC Land Cover in Central Asia 2009








MODIS Land Cover in 2009








Zoom: Irrigation Region Khorezm







Accuracies C5.0 for improved sampling




class	C5 user's accuracy	C5 producer's accuracy
cultivated and managed terrestrial area	92.8	94.1
cultivated aquatic or regularly flooded area	93.6	90.7
needleleaved evergreen trees	80.8	80.8
broadleaved deciduous trees	92.7	93.1
sparse shrubs and sparse herbaceous	963	96.6
herbaceous closed to open vegetation	910	91.3
dosed to open shrubland	94 5	94.0
open shrubland	94 1	94 3
bare area, unconsolidated materials	96.5	96.2
bare area, unconsolidated materials with salt flats	95.8	95.8
ıce	75 1	77.4
waterbodies	983	98.6



Usage of SRTM







Thank You



